



Ethyl Alcohol (Ethanol) Wipes Product# 1606-30PK

Product Description

Convenient, lint-free wipes, pre-saturated with denatured alcohol (90% ethanol, 5% IPA, 5% water).

Ethyl alcohol (CAS #64-17-5) is also referred to as ethanol. It dissolves a wide range of polar and non-polar soils, including light oils, fingerprints, cutting fluids, flux residues, carbon deposits, and mold release. For electronic printed circuit board (PCB) assembly, you will find Ethyl Alcohol Wipes can be used to clean flux residues from recently soldered circuit boards or in PCB repair and rework.

- Lower odor than isopropyl alcohol (IPA)
- Fast evaporation – 4X faster than IPA
- Plastic-safe
- Lint-free & tear resistant

Applications

- Mobile devices
- Electronics cleaning
- Tool kits
- Field service
- Device refurbishing and workspace clean-up



Typical Product Data and Physical Properties

Physical State:	Liquid
Odor:	Mild alcohol odor
Appearance:	Clear, Colorless liquid
pH:	N/A
Percent Volatile:	100
Specific Gravity:	0.82 @ 16°C
Flashpoint and Method:	61°F (16°C) Closed Cup
Shelf life:	5 years

Packaging and Availability

1606-30PK 30 ct. individually wrapped
10 boxes / case

Packaged for sale in more than 30 countries.
Packaged to ship as not regulated; non-hazardous.

Wipe Specifications

- Nonwoven cellulose-poly material
- 5.5"x5.5" (140mm x 140mm)
- 3g ethanol/packet



Ethyl Alcohol (Ethanol) Wipes Product# 1606-30PK

Usage Instructions

Remove a saturated lint-free cloth from the container. Wipe surface with cloth, rotating the cleaning side of the wipe periodically. **Note:** Ethanol is considered plastic safe. However, test on inconspicuous area of plastic parts or sensitive coated substrates, before using freely.

Environmental Policy

Techspray® is committed to developing products to ensure a safer and cleaner environment. We will continue to meet and sustain the regulations of all federal, state and local government agencies.

Resources

Techspray® products are supported by global sales, technical and customer services resources.

For additional technical information on this product or other Techspray® products in the United States, call the technical sales department at 800-858-4043, email tsales@techspray.com or visit our web site at: www.techspray.com.

Important Notice to Purchaser/User: The information in this publication is based on tests that we believe are reliable. The results may vary due to differences in tests type and conditions. We recommend that each user evaluate the product to determine its suitability for the intended application. Conditions of use are outside our control and vary widely. Techspray's only obligation and your only solution is replacement of product that is shown to be defective when you receive it. In no case will Techspray® be liable for any special, incidental, or consequential damages based on breach of warranty, negligence or any other theory.